

Pricing, Dimensions & Weights

AF-300G11

HP Rating	NEMA Enclosure	Rated Output Current (A)	Overload (150% 1min.)	AF-300G11 Model No.	Catalog No.	* List Price GO-5G11	Dimensions H x W x D (inches)	Weight (lbs)
230VAC, 3 phase, 50/60Hz Input, NEMA1								
0.25	1	1.5	2.3	6KG1123F25X1A1	D6501	740	10.24 x 4.33 x 5.12	4.8
0.5	1	3	4.5	6KG1123F50X1A1	D6502	755	10.24 x 4.33 x 5.12	4.8
1	1	5	7.5	6KG1123001X1A1	D6503	800	10.24 x 4.33 x 5.71	5.5
2	1	8	12	6KG1123002X1A1	D6504	860	10.24 x 5.91 x 5.71	8.4
3	1	11	17	6KG1123003X1A1	D6505	925	10.24 x 5.91 x 5.71	8.4
5	1	17	26	6KG1123005X1A1	D6506	1140	10.24 x 5.91 x 5.71	8.4
7.5	1	25	38	6KG1123007X1A1	D6507	1420	10.24 x 8.66 x 7.68	13.4
10	1	33	50	6KG1123010X1A1	D6508	1725	10.24 x 8.66 x 7.68	13.4
15	1	46	69	6KG1123015X1A1	D6509	2310	15.75 x 9.84 x 7.68	22.0
20	1	59	89	6KG1123020X1A1	D6510	2915	15.75 x 9.84 x 7.68	22.0
25	1	74	111	6KG1123025X1A1	D6511	3460	15.75 x 9.84 x 7.68	23.1
30	1	87	131	6KG1123030X1A1	D6512	4000	15.75 x 9.84 x 7.68	23.1
40	1	115	173	6KG1123040X1A1	D6513	6435	29.7 x 13.5 x 10.0	70
50	1	145	218	6KG1123050X1A1	D6514	8050	33.1 x 14.9 x 10.6	86
60	1	180	270	6KG1123060X1A1	D6515	9815	38.0 x 14.9 x 10.6	106
75	1	215	323	6KG1123075X1A1	D6516	13130	38.0 x 14.9 x 10.6	110
100	1	283	425	6KG1123100X1A1	D6517	22175	41.3 x 21.0 x 11.2	172
125	1	346	519	6KG1123125X1A1	D6518	26500	50.4 x 26.9 x 14.2	282

230VAC, 3 phase, 50/60Hz Input, NEMA4

0.25	4	1.5	2.3	6KG1123F25X4A1	D6551		10.24 x 4.33 x 5.12	4.8
0.5	4	3	4.5	6KG1123F50X4A1	D6552		10.24 x 4.33 x 5.12	4.8
1	4	5	7.5	6KG1123001X4A1	D6553		10.24 x 4.33 x 5.71	5.5
2	4	8	12	6KG1123002X4A1	D6554		10.24 x 5.91 x 5.71	8.4
3	4	11	17	6KG1123003X4A1	D6555		10.24 x 5.91 x 5.71	8.4
5	4	17	26	6KG1123005X4A1	D6556		10.24 x 5.91 x 5.71	8.4
7.5	4	25	38	6KG1123007X4A1	D6557		10.24 x 8.66 x 7.68	13.4
10	4	33	50	6KG1123010X4A1	D6558		10.24 x 8.66 x 7.68	13.4

230VAC, 3 phase, 50/60Hz Input, NEMA12

15	12	46	69	6KG1123015X2A1	D6559		15.75 x 9.84 x 7.68	22.0
20	12	59	89	6KG1123020X2A1	D6560		15.75 x 9.84 x 7.68	22.0
25	12	74	111	6KG1123025X2A1	D6561		15.75 x 9.84 x 7.68	23.1
30	12	87	131	6KG1123030X2A1	D6562		15.75 x 9.84 x 7.68	23.1

230VAC, 3 phase, 50/60Hz Input, Open

40	Open	115	173	6KG1123040X9A1	---	6075	21.7 x 13.4 x 10.0	64
50	Open	145	218	6KG1123050X9A1	---	7125	24.2 x 14.8 x 10.6	79
60	Open	180	270	6KG1123060X9A1	---	8695	29.1 x 14.8 x 10.6	97
75	Open	215	323	6KG1123075X9A1	---	11750	29.1 x 14.8 x 10.6	101
100	Open	283	425	6KG1123100X9A1	---	21025	29.5 x 20.9 x 11.2	154
125	Open	346	519	6KG1123125X9A1	---	24900	34.6 x 26.8 x 14.2	253

* Highlight indicates products that will be available at a future date.

Pricing, Dimensions & Weights**AF-300G11**

HP Rating	NEMA Enclosure	Rated Output Current (A)	Overload (150% 1min.)	AF-300G11 Model No.	Catalog No.	* List Price GO-5G11	Dimensions H x W x D (inches)	Weight (lbs)
230VAC, 3 phase, 50/60Hz Input, Open with NEMA12 Heatsink								
40	Open	115	173	6KG1123040X8A1	---	6315	21.7 x 13.4 x 10.0	64
50	Open	145	218	6KG1123050X8A1	---	7495	24.2 x 14.8 x 10.6	79
60	Open	180	270	6KG1123060X8A1	---	9195	29.1 x 14.8 x 10.6	97
75	Open	215	323	6KG1123075X8A1	---	12505	29.1 x 14.8 x 10.6	101
100	Open	283	425	6KG1123100X8A1	---	21600	29.5 x 20.9 x 11.2	154
125	Open	346	519	6KG1123125X8A1	---	25700	34.6 x 26.8 x 14.2	253

460VAC, 3 phase, 50/60Hz Input, NEMA1

0.5	1	1.5	2.3	6KG1143F50X1A1	D6519	990	10.24 x 4.33 x 5.12	4.8
1	1	2.5	3.8	6KG1143001X1A1	D6520	1025	10.24 x 4.33 x 5.71	5.5
2	1	3.7	5.6	6KG1143002X1A1	D6521	1095	10.24 x 5.91 x 5.71	8.4
3	1	5.5	8.3	6KG1143003X1A1	D6522	1180	10.24 x 5.91 x 5.71	8.4
5	1	9	14	6KG1143005X1A1	D6523	1450	10.24 x 5.91 x 5.71	8.4
7.5	1	13	20	6KG1143007X1A1	D6524	1815	10.24 x 8.66 x 7.68	14.3
10	1	18	27	6KG1143010X1A1	D6525	2195	10.24 x 8.66 x 7.68	14.3
15	1	24	36	6KG1143015X1A1	D6526	2950	15.75 x 9.84 x 7.68	22.0
20	1	30	45	6KG1143020X1A1	D6527	3725	15.75 x 9.84 x 7.68	22.0
25	1	39	59	6KG1143025X1A1	D6528	4420	15.75 x 9.84 x 7.68	23.1
30	1	45	68	6KG1143030X1A1	D6529	5150	15.75 x 9.84 x 7.68	23.1
40	1	60	90	6KG1143040X1A1	D6531	5850	29.7 x 13.5 x 10.0	70
50	1	75	113	6KG1143050X1A1	D6532	7100	29.7 x 14.9 x 10.6	82
60	1	91	137	6KG1143060X1A1	D6533	8360	34.6 x 14.9 x 10.6	95
75	1	112	168	6KG1143075X1A1	D6534	10290	34.6 x 14.9 x 10.6	97
100	1	150	225	6KG1143100X1A1	D6535	12980	38.0 x 14.9 x 10.6	115
125	1	176	264	6KG1143125X1A1	D6536	16370	38.0 x 21.0 x 12.4	174
150	1	210	315	6KG1143150X1A1	D6537	18350	38.0 x 21.0 x 12.4	245
200	1	253	380	6KG1143200X1A1	D6538	22400	53.1 x 21.0 x 14.2	245
250	1	304	456	6KG1143250X1A1	D6539	26100	53.1 x 21.0 x 14.2	245
300	1	377	566	6KG1143300X1A1	D6540	31340	55.1 x 26.9 x 14.2	337
350	1	415	623	6KG1143350X1A1	D6541	37500	55.1 x 26.9 x 14.2	337
400	1	520	780	6KG1143400X1A1	D6542			
450	1	585	878	6KG1143450X1A1	D6543			

460VAC, 3 phase, 50/60Hz Input, NEMA4

0.5	4	1.5	2.3	6KG1143F50X4A1	D6569		10.24 x 4.33 x 5.12	4.8
1	4	2.5	3.8	6KG1143001X4A1	D6570		10.24 x 4.33 x 5.71	5.5
2	4	3.7	5.6	6KG1143002X4A1	D6571		10.24 x 5.91 x 5.71	8.4
3	4	5.5	8.3	6KG1143003X4A1	D6572		10.24 x 5.91 x 5.71	8.4
5	4	9	14	6KG1143005X4A1	D6573		10.24 x 5.91 x 5.71	8.4
7.5	4	13	20	6KG1143007X4A1	D6574		10.24 x 8.66 x 7.68	14.3
10	4	18	27	6KG1143010X4A1	D6575		10.24 x 8.66 x 7.68	14.3

460VAC, 3 phase, 50/60Hz Input, NEMA12

15	12	24	36	6KG1143015X2A1	D6576		15.75 x 9.84 x 7.68	22.0
20	12	30	45	6KG1143020X2A1	D6577		15.75 x 9.84 x 7.68	22.0
25	12	39	59	6KG1143025X2A1	D6578		15.75 x 9.84 x 7.68	23.1
30	12	45	68	6KG1143030X2A1	D6579		15.75 x 9.84 x 7.68	23.1

* Highlight indicates products that will be available at a future date.

Pricing, Dimensions & Weights**AF-300G11**

HP Rating	NEMA Enclosure	Rated Output Current (A)	Overload (150% 1min.)	AF-300G11 Model No.	Catalog No.	* List Price GO-5G11	Dimensions H x W x D (inches)	Weight (lbs)
460VAC, 3 phase, 50/60Hz Input, Open								
40	Open	60	90	6KG1143040X9A1	---	5500	21.7 x 13.4 x 10.0	64
50	Open	75	113	6KG1143050X9A1	---	6755	21.7 x 14.8 x 10.6	75
60	Open	91	137	6KG1143060X9A1	---	7920	26.6 x 14.8 x 10.6	86
75	Open	112	168	6KG1143075X9A1	---	9980	26.6 x 14.8 x 10.6	88
100	Open	150	225	6KG1143100X9A1	---	12600	29.1 x 14.8 x 10.6	106
125	Open	176	264	6KG1143125X9A1	---	15350	29.1 x 20.9 x 12.4	154
150	Open	210	315	6KG1143150X9A1	---	17300	29.1 x 20.9 x 12.4	154
200	Open	253	380	6KG1143200X9A1	---	21050	39.4 x 20.9 x 14.2	220
250	Open	304	456	6KG1143250X9A1	---	25250	39.4 x 20.9 x 14.2	220
300	Open	377	566	6KG1143300X9A1	---	29400	39.4 x 26.8 x 14.2	308
350	Open	415	623	6KG1143350X9A1	---	35300	39.4 x 26.8 x 14.2	308
400	Open	520	780	6KG1143400X9A1	---			
450	Open	585	878	6KG1143450X9A1	---			

460VAC, 3 phase, 50/60Hz Input, Open with NEMA12 Heatsink

40	Open	60	90	6KG1143040X8A1	---	5675	21.7 x 13.4 x 10.0	64
50	Open	75	113	6KG1143050X8A1	---	6920	21.7 x 14.8 x 10.6	75
60	Open	91	137	6KG1143060X8A1	---	8180	26.6 x 14.8 x 10.6	86
75	Open	112	168	6KG1143075X8A1	---	10160	26.6 x 14.8 x 10.6	88
100	Open	150	225	6KG1143100X8A1	---	12790	29.1 x 14.8 x 10.6	106
125	Open	176	264	6KG1143125X8A1	---	15820	29.1 x 20.9 x 12.4	154
150	Open	210	315	6KG1143150X8A1	---	17800	29.1 x 20.9 x 12.4	154
200	Open	253	380	6KG1143200X8A1	---	21700	39.4 x 20.9 x 14.2	220
250	Open	304	456	6KG1143250X8A1	---	26030	39.4 x 20.9 x 14.2	220
300	Open	377	566	6KG1143300X8A1	---	29800	39.4 x 26.8 x 14.2	308
350	Open	415	623	6KG1143350X8A1	---	36380	39.4 x 26.8 x 14.2	308
400	Open	520	780	6KG1143400X8A1	---			
450	Open	585	878	6KG1143450X8A1	---			

* Highlight indicates products that will be available at a future date.